GLOBALGOODS SOLUTION

ISO 9001:2015 Certified
IEC & DGFT Registered Exporter
www.globalgoodssoln.com

PRODUCT CATALOGUE

Industrial Rubber Sheets & Gaskets

Rubber sheets in rolls and gaskets cut to size for plant maintenance, flange sealing, tank and chute lining and insulation. Polymer, hardness, thickness and finish are matched to your service conditions, and every order is supplied with a Material Test Certificate.

10+	1 – 50 mm	40 – 90	1 / 1.2 / 1.5 m
RUBBER GRADES	THICKNESS RANGE	HARDNESS SHORE A	ROLL WIDTHS

RUBBER SHEET RANGE




General Purpose (NR / SBR)

Economical sheeting for packing, gaskets, floor coverings and insulation.




Abrasion Resistant (NR)

High-resilience natural rubber for tank, pipe and chute lining in mining and cement.



Nitrile (NBR)

Oil and fuel resistant sheeting for refineries, drilling rigs and oil-exposed gaskets.



EPDM & Waterproofing

Ozone, weather and heat resistant sheeting for outdoor gaskets and membranes.



Neoprene (CR)

Weather and moderate oil resistance for marine and outdoor service.



Silicone

Stable from -60°C to +200°C for gaskets, seals and pressure pads.



Butyl (IIR) & Hypalon (CSM)

Airtight, chemically resistant sheeting for chemical and fertilizer plants.



Food Grade

Non-toxic, odourless sheeting in NR, NBR, EPDM and CR for food and pharma use.



Insertion Jointing & Sponge

Fabric-reinforced jointing sheets and sponge rubber for flanges and vibration isolation.

RUBBER GASKETS — CUT TO SIZE

Full-face and ring (IBC) flange gaskets cut from any grade above, to ASME B16.21 / B16.5 flange dimensions, EN 1514 or your drawing. Supplied as loose gaskets or packed per flange together with stud bolts and nuts as complete flange kits for shutdowns.



TECHNICAL REFERENCE

Rubber Sheet Specifications

Typical values by polymer, for specification planning. Exact hardness, thickness and properties are confirmed per order and backed by a Material Test Certificate at dispatch.

Type	Polymer	Hardness (Shore A)	Temperature Range	Key Resistance
General Purpose	NR / SBR	65 – 75	-20°C to +70°C	Water, mild abrasion
Abrasion Resistant	NR	40 – 65	-30°C to +70°C	Slurry, impact, wear
Nitrile	NBR	60 – 75	-30°C to +110°C	Oils, fuels, greases
EPDM	EPDM	55 – 70	-40°C to +150°C	Ozone, weather, steam, hot water
EPDM Membrane	EPDM	60 – 65	-30°C to +130°C	Waterproofing, UV
Neoprene	CR	60 – 75	-30°C to +130°C	Weather, moderate oils
Silicone	VMQ	50 – 60	-60°C to +200°C	Extreme temperature
Viton	FKM	70 – 80	-20°C to +200°C	Acids, fuels, chemicals
Butyl	IIR	55 – 65	-30°C to +130°C	Gases, chemicals
Hypalon	CSM	60 – 70	-30°C to +130°C	Acids, oxidising agents
Food Grade	NR / NBR / EPDM / CR	60 – 65	-25°C to +130°C	Food and pharma contact
Insertion Jointing	NR / SBR + fabric	50 – 80	Reference: IS 638	

THICKNESS — 1 to 25 mm standard; up to 50 mm for selected polymers.

ROLLS — 1 / 1.2 / 1.5 m wide, 10 m long; sheets and cut pieces on request.

FINISH — Smooth, fabric-inserted, or patterned (diamond / ribbed).

REFERENCE STANDARDS — ASTM D2000 material classification, IS 638 insertion jointing, ASTM D6134 / EN 13956 waterproofing membranes, ASME B16.21 non-metallic flat gaskets.

TYPICAL END USES

Flange Gaskets & Seals · Tank & Pipe Lining · Chute & Hopper Lining · Steel & Mining Plants · Chemical & Fertilizer Plants · Power & Desalination · Food & Pharma · Roofing & Waterproofing

WHY BUY FROM US

- Polymer matched to your chemical and temperature service
- Material Test Certificate with every order
- Rolls, sheets or cut gaskets in one shipment
- Combine with valves, stud bolts and nuts in one order

SEND WITH YOUR RFQ

- Polymer / grade and service medium
- Thickness, hardness and finish
- Roll size or gasket drawing / flange size
- Quantity and destination port

ABOUT GLOBALGOODS SOLUTION

Approved vendor to major Gulf steel and petrochemical companies, 70+ export shipments. Also supplying industrial valves, stud bolts & nuts.

COMPANY
GlobalGoods Solution (OPC) Private Limited

REGISTERED OFFICE
493/14A, Kanjiramvila Thekkethil, Kundayam Road, Pathanapuram – 689695, Kerala, India

PHONE / WHATSAPP
+91 73064 21089

EMAIL
info@globalgoodssoln.com

WEBSITE
www.globalgoodssoln.com

SEND YOUR RFQ BY EMAIL OR WHATSAPP